CUTTING WIDTH

unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines

shown herein without



20' SUPER PREDATOR



Triple Center Axles are standard on the 20' Super Predator, Shown here with standard used aircraft tires.



Our updated hydraulic phasing level lift system is a superior improvement over the outdated mechanical lift system.









notice or obligation. THE 20' SUPER PREDATOR HAS A 255 HP TRANSFER GEARBOX WITH 210 HP CENTER AND WING GEARBOXES.

FRONT AND REAR CHAINS, DUAL WING WHEELS, HYDRAULIC LEVEL LIFT, AND USED AIRCRAFT TIRES ARE STANDARD EQUIP-MENT ON THE 20' SUPER PREDATOR.



ITEM NUMBERS 001-1521-4

540 001-1520-4 1000

SPECIFICATIONS

Cutting Width. 238" Transport Width..... 105" Overall Width..... 246" Overall Length..... 204" Cutting Height 2"-15" Blade Overlap 5" Wing Lift Hydraulics. . . Standard Wing Flex. 90° Up/22° Down Jackstand Standard Hitch Swivel Clevis Blade Carrier Pan Stump **Jumpers** Minimum PTO

Divider Box*..... 255 hp Outboard Gearbox or Center & Wings* . . . 210 hp Output Shaft Diameter. 2" Cut Capacity 3" **BLADE TIP SPEED:** Main or Center 540 15,992 FPM 1000 16,052 FPM Wings 540 15,384 FPM 1000 15,484 FPM DRIVELINE SIZE: Main.... Cat. 5 Constant Veloc.

Outboard Center or Wings Cat. 4 w/Slip Clutch Deck Thickness 3/16" Side Skirt 1/4" x 10 1/4" Replaceable Skid ShoesStandard Safety Chains Standard (Front & Rear) Weight (Approx)..... 6900 lbs. Standard Tires Used Aircraft Tires Dual Wingwheels. . . . Standard Deck Rings to Protect Deck Standard



Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.

HP Required 75 hp

Main Gearbox or