o Galvanize

**CUTTING WIDTH** 



## 15' PREDATOR



Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.



This unit is equipped with two 16,000 lb leveling ratchet jacks.



with 210 hp center and

wing gearboxes.

255 hp transfer gear box



## SPECIFICATIONS

Cutting Width	180"
Transport Width	90"
Overall Width	187"
Overall Length	180"
Cutting Height	2"-15"
Blade Overlap	6"
Wing Lift Hydraulics	Standard
Wing Flex	90° Up/22°
Down	
Jackstand	Standard
Hitch	Swivel Clevis
Blade Carrier	Pan Stump

**Jumpers** 

Minimum PTO HP Required . . . . . 55 hp

or Divider Box*	2	255 hp
Outboard Gearbox		
or Center & Wings*	2	10 hp
Output Shaft Diame	ter. 2	-3/8"
Cut Capacity 3-1/2"		
Blade Tip Speed:		
Main or Center	540	15,268 FPM
	1000	15,072 FPM
Wings	540	14,821 FPM
	1000	14,946 FPM

Driveline Size:

Main Gearbox

Main.... Cat. 5 Constant Veloc.

\*\* The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.

Outboard Center	
or Wings	Cat. 4 w/Slip
_	Clutch

Deck Thickness . . . . . 3/16" Side Skirt . . . . . . . . . 1/4" x 10 1/4"

Replaceable Skid

Shoes ..... Standard Front Safety Chains... Standard

Rear Safety Deflectors Rubber Guard

Standard with Chain Option

Weight (Approx)..... 5600 lbs. Standard Tires . . . . . Laminated

600 x 9 Dual Wingwheels.... Option

Deck Rings to

Protect Deck . . . . . . Standard

Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.