

SUPER HIGHWAY SPECIAL 6' & 7'


CAT. 5 DRIVELINE
**6' CUTTING WIDTH
72"**
**7' CUTTING WIDTH
84"**
**ITEM NUMBERS
001-0130-SH-CAT
001-0137-SH-CAT**

- 3/4" A-Frames
- Cat. I & Cat II Hitch
- Quick Hitch Compatible
- Dual tailwheel option available
- New reinforced tailwheel bracket


Features:

- 1/2" gearbox plate
- Heavy duty A-Frame
- New rounded rear deck
- 1/2" x 4" Heavy Duty High Vacuum blades
- 3/8" Deck ring (standard)
- Counter sunk bolt on skid plate
- Upgraded 95 hp gearbox rating
- Heavy duty stump jumper with laminated tailwheel
- Extra Heavy Duty four plate slip clutch protection with flexible top link
- 140 hp gearbox option available


HOT-DIPPED GALVANIZED DECK & FRAME

FRONT & REAR CHAIN GUARD OPTIONAL


Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.

SPECIFICATIONS

Cutting Width	72"-84"	Minimum PTO HP Required		Deck Thickness	3/16"
Transport Width	79"-90"	72"	40 hp	Front Safety Deflectors: Chain Option	
Overall Width	79"-90"	84"	45 hp	Rear Safety Deflectors: Rubber Guard Standard with Chain Option	
Overall Length	91"-100"	Gearbox Rating*	95 hp - 140 hp option	Weight (Approx):	
Overall Height	2" - 10"	Cut Capacity	3"	72"	1185 lbs.
Hitch	Quick Attach Cat. I & Cat II	Blade Tip Speed:		84"	1385 lbs.
Blade Carrier	Pan Stump Jumpers	72"	14.995 FPM	Standard Tires	Laminated
		84"	17.495 FPM	Dual Tailwheels	Option
		Driveline Size	Cat. 5 w/Slip Clutch	Side Skirt	1/4" x 8"
				Deck Rings to Protect Deck	Standard

* Gearbox ratings based on field performance.

** The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.

Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.