

# 15' VIPER

**INTRODUCING... THE 15' VIPER WITH FORMED OUTRIGGERS AND SELF-CLEANING SMOOTH DOUBLE DECK.**



**ITEM NUMBERS**  
001-1508      540  
001-1508-2      1000

Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.



**CUTTING WIDTH 180"**

\* Gearbox ratings based on field performance.

\*\* The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.

## SPECIFICATIONS

Cutting Width..... 180"	Output Shaft Diameter..... 2-7/8"	Replaceable Skid Shoes ..... Standard
Transport Width..... 90"	Cut Capacity .....4"	Front & Rear Safety Chains ..... Standard
Overall Width..... 187"	Blade Tip Speed	Weight (Approx)..... 6250 lbs.
Overall Length..... 228"	Main or Center	Galvanized Deck & Frame..... Standard
Cutting Height ..... 2"-18"	540..... 15,980 FPM	Standard Tires ..... 25" Diameter
Blade Overlap ..... 6-1/2"	1000..... 15,974 FPM	Laminate (Standard)   Option (Used Aircraft Tires)
Wing Lift Hydraulics..... Standard	Wings	Dual Tailwheels..... Standard
Wing Flex..... 90° Up/22° Down	540..... 16,113 FPM	Mechanical Level Lift..... Standard
Jackstand ..... Standard	1000..... 15,707 FPM	
Hitch ..... Swivel Clevis	Driveline Size:	
Blade Carrier ..... Pan Stump Jumpers	Main..... Cat. 6 Constant Velocity	
Minimum PTO HP Required.....55 hp	Outboard Center or Wings ..... Cat. 5 w/ Slip Clutch	
Main Gearbox or Divider Box* .....275 hp	Deck Thickness ..... 3/16"	
Outboard Gearbox or Center & Wings* ..... 240 hp	Side Skirt ..... 1/2" x 11"	