


# 12' VIPER



**CUTTING WIDTH**  
**144"**



**Features:**

- 160 hp transfer gear box with 120 hp center and wing gearboxes
- Best in class cut capacity
- Smooth top deck
- Requires only one hydraulic outlet
- Replaceable skid shoes
- Faster blade tip speed
- All 3" cylinders
- High Lift Blades

**ITEM NUMBER**  
**001-1202**

Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.

\* Gearbox ratings based on field performance.

\*\* The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.



## SPECIFICATIONS

Cutting Width. . . . .	144"	Minimum PTO		Outboard Center	
Transport Width. . . . .	90"	HP Required . . . . .	45 hp	or Wings . . . . .	Cat. 4 w/Slip Clutch
Overall Width. . . . .	151"	Main Gearbox		Deck Thickness. . . . .	3/16"
Overall Length. . . . .	159"	or Divider Box*. . . . .	160 hp	Side Skirt. . . . .	1/4" x 11"
Cutting Height . . . . .	2"-12"	Outboard Gearbox		Replaceable Skid Shoes	Standard
Blade Overlap . . . . .	6"	or Center & Wings*. . . . .	120 hp	Front Safety Chains. . . . .	Standard
Wing Lift Hydraulics. . . . .	Standard	Output Shaft Diameter. . . . .	2"	Rear Safety Chains . . . . .	Standard
Wing Flex. . . . .	90° Up/22° Down	Cut Capacity . . . . .	3"	Weight (Approx). . . . .	3,175 lbs.
Jackstand . . . . .	Standard	Blade Tip Speed:		Standard Tires. . . . .	Laminated 600 x 9
Hitch . . . . .	Swivel Clevis	Main or Center	540 . 16,362 fpm	Mechanical Level Lift.....	Standard
Blade Carrier . . . . .	Pan Stump Jumpers	Wings	540 . 15,708 fpm		
		Driveline Size:			
		Main. . . . .	Cat. 5 Constant Veloc.		