

20' PREDATOR



This unit is equipped with a 16,000 lb leveling ratchet jack.



Smooth underdecks make for more efficient mowing and less area for rust to begin. Deck rings are standard.



Triple Center Axles are standard on the 20' Predator. Shown here with optional used aircraft tires.

BASE UNIT SHOWN WITH LAMINATED TIRES



DUAL WING WHEELS ARE STANDARD EQUIPMENT ON THE 20' PREDATOR.

CUTTING WIDTH
238"



* Gearbox ratings based on field performance.

** The Galvanized gloss level could vary from unit to unit. Modern Ag Products reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.

ITEM NUMBERS
001-1521 540
001-1520 1000

SPECIFICATIONS

Cutting Width. 238"	Main Gearbox or Divider Box* 255 hp	Outboard Center or Wings. Cat. 4 w/Slip Clutch
Transport Width. 105"	Outboard Gearbox or Center & Wings* . . . 210 hp	Deck Thickness 3/16"
Overall Width. 246"	Output Shaft Diameter. 2"	Side Skirt. 1/4" x 10 1/4"
Overall Length. 204"	Cut Capacity 3"	Replaceable Skid
Cutting Height 2"-15"	Blade Tip Speed:	Shoes Standard
Blade Overlap 5"	Main or Center 540 15,992 FPM	Front Safety Chains. . . Standard
Wing Lift Hydraulics. . . Standard	1000 16,052 FPM	Rear Safety Deflectors: Chain Guard Standard
Wing Flex. 90° Up/22° Down	Wings 540 15,384 FPM	Weight (Approx). 6750 lbs
Jackstand Standard	1000 15,484 FPM	Standard Tires. Laminated 600 x 9
Hitch Swivel Clevis	Driveline Size:	Dual Wingwheels. . . . Standard
Blade Carrier Pan Stump Jumpers	Main. Cat. 5 Constant Veloc.	Deck Rings to Protect Deck Standard
Minimum PTO HP Required 75 hp		

Item numbers are base models only, pictures may show models with some options included. Please ask your sales representative for information on base models and models with options.